



40 mm x 68 mm x 15 mm Mass bearing SKF S7008 CE/P4BVG275 Double-Row Angular Contact Ball Bearings

Bearing No. S7008 CE/P4BVG275

S7008 CE/P4BVG275 Bearing 2D drawings and 3D
CAD models

d	40 mm
D	68 mm
B	15 mm
d ₁	49.7 mm
d ₂	47.6 mm
D ₂	60.85 mm
r _{1,2} min.	1 mm
r _{3,4} min.	0.6 mm
a	14.8 mm
d _a min.	44.6 mm
d _a max.	49.1 mm
d _b min.	44.6 mm
d _b max.	47 mm
D _a max.	63.4 mm
D _b max.	63.8 mm
r _a max.	1 mm
r _b max.	0.6 mm
Basic dynamic load rating C	12.4 kN
Basic static load rating C ₀	7.65 kN
Fatigue load limit P _u	0.32 kN
Attainable speed for grease lubrication	30000 r/min
Ball diameter D _w	7.144 mm
Number of balls z	19
Preload class A G _A	65 N



Nice Precision Bearings (India) Pvt. Ltd

Static axial stiffness, preload class A	34 N/ μ m
Preload class B G_B	200 N
Static axial stiffness, preload class B	54 N/ μ m
Preload class C G_C	390 N
Static axial stiffness, preload class C	73 N/ μ m
Calculation factor f	1.06
Calculation factor f_1	1
Calculation factor f_{2A}	1
Calculation factor f_{2B}	1.03
Calculation factor f_{2C}	1.05
Calculation factor f_{HC}	1
Calculation factor f_0	8.1
Mass bearing	0.19 kg